



# OAC Plate Compactors



Okada boom mounted plate compactors let you expand the versatility of your backhoe or excavator, and there is an Okada model that is precision engineered to perfectly match the capabilities of your carrier. Rugged construction and proven compaction technology make quick work of any compaction or driving task, keep your crew safely out of the trench and eliminate the need for expensive shoring, while the minimal maintenance requirements keep you working.



The OAC Series line of compactors provide solutions with superior power and efficiency for all your compaction tasks, and help ensure you meet Proctor soil density requirements.

**Available Options**

- Flow control manifold
- Quick attach mounting system available for most models
- Base plate extension for narrow trenches
- Custom mounting specifications



**Specifications**

[050107]

Model	Unit	OAC100	OAC200	OAC300	OAC400	OAC500
Impulse force	lbs	3150	6500	13500	20000	22000
Frequency	cpm	2100	2000	2000	2000	2100
Hydraulic flow	gpm	10	20	30	40	50
Pressure	psi	2200	2200	2200	2200	2200
Weight	inches	370	840	1500	2200	2200
Bottom plate	inches	11.5x30	23x34	28x44	34x43	34x43
Height	inches	18	30	37	42	42
Pin diameter	inches	Carrier specific	Carrier specific	Carrier specific	Carrier specific	Carrier specific
Lift compaction	ft	1-3	2-4	3-5	5-7	5-7
Carrier wt. range	tons	2-7	6-9	10-20	20-28	28-43
	lbs	4400-15400	13200-19800	22000-44000	44000-61600	61600-94600

\*\* Specifications are subject to change without prior notification.



**Okada America Inc.**

12950 SE Hwy. 212 Bldg. D  
 Clackamas, OR 97015  
 Tel 503-557-7033  
 Fax 503-557-7779

904 Medina Rd.  
 Medina, OH 44256  
 Tel 330-239-2666  
 Fax 330-239-3670

115 Commerce Blvd.  
 Cleburne, TX 76033  
 Tel 817-774-1295

[www.okadaamerica.com](http://www.okadaamerica.com)